

FABRIC TECHNICAL SPECIFICATIONS

- 100% polyester high strength technical fabric (*minimum 1100 gr/m²*)
- Colour : sand.
- European origin.
- KTW certification – Food grade compliant
- UV treatment in the mass
- Temperature resistance from -30°C to +70°C.
- Tear resistance 700 N (*minimum*).
- Tensile strength resistance 400 daN/5cm (*minimum*).

STANDARD ACCESSORIES

Capacities ≤ 50m³

- 1 SIMPLE VENT - Central vent with cap Ø 150mm - Ref 25.533 - (1)
- 2 SIDE INLET / OUTLET 2" - Flange (PPG) + ¼ turn valve (Brass) + Guillemin coupling with plug (Alu) - Ref 108.778 - (2)

Capacities > 50m³

- 1 SIMPLE VENT - Central vent with cap Ø 150mm - Ref 25.533 - (1)
- 2 SIDE INLET / OUTLET 3" - Flange (PPG) + ¼ turn valve (Brass) + Guillemin coupling with plug (Alu) - Ref 109.013 - (2)

Other

- 4 REINFORCEMENT PLATES AT THE CORNERS (3)
- 1 REPAIR KIT (4)
- 1 IDENTIFICATION MARKING (5)

Notice about accessories parts mounting :

- ACCESSORIES ≤ DN50: Flange, counter flange, valve, coupling delivered to the customer assembled (does not matter what the tank size and accessories locations are)
- ACCESSORIES > DN50: Flange & counter flange assembled // valve + coupling not assembled
- OVERFLOW : Always delivered not assembled

3D REPRESENTATION OF THE TANK



1



4



2



3





DIMENSIONAL CHARACTERISTICS

FLEXIBLE TANK

Volume (m³)	Width (m)	Lenght (m)	Height (m)	Weight (Kg)
1	1,86	1,87	0,50	12 Kg
2	1,86	3,32	0,50	18 Kg
3	2,14	4,05	0,50	23 Kg
4	2,14	5,25	0,50	28 Kg
5	3,21	3,24	0,80	27 Kg
6	3,21	3,75	0,80	30 Kg
7	3,21	4,27	0,80	34 Kg
8	3,21	4,71	0,90	37 Kg
9	3,21	5,02	0,90	39 Kg
10	4,28	4,38	0,90	45 Kg
12	4,28	4,79	1,10	49 Kg
15	4,28	5,29	1,10	54 Kg
20	4,28	6,44	1,10	65 Kg
25	5,35	6,31	1,10	79 Kg
30	5,35	7,19	1,20	90 Kg
35	5,35	8,24	1,20	102 Kg
40	5,35	8,75	1,30	108 Kg
45	6,42	8,01	1,30	119 Kg
50	6,42	9,76	1,30	129 Kg
55	6,42	9,50	1,30	140 Kg
60	6,42	9,80	1,40	144 Kg
65	6,42	10,49	1,40	154 Kg
70	7,49	9,51	1,40	163 Kg
80	7,49	10,67	1,40	182 Kg
90	7,49	11,68	1,50	199 Kg
100	7,49	12,77	1,50	218 Kg
110	8,56	12,07	1,50	235 Kg
115	8,56	12,53	1,50	244 Kg
120	8,56	13,00	1,50	253 Kg
125	8,56	13,46	1,50	261 Kg
130	8,56	13,92	1,50	270 Kg
135	9,63	12,76	1,50	279 Kg
140	9,63	13,17	1,50	287 Kg
150	9,63	13,97	1,50	305 Kg
160	9,63	14,78	1,50	322 Kg
165	10,70	13,66	1,50	331 Kg
180	10,70	14,73	1,50	356 Kg
200	11,77	14,69	1,50	391 Kg
240	12,84	15,81	1,50	458 Kg
250	12,84	16,39	1,50	475 Kg
300	13,91	17,81	1,50	559 Kg
350	14,98	19,01	1,50	641 Kg
360	14,98	19,50	1,50	658 Kg
400	16,05	20,94	1,50	756 Kg
450	17,12	22,07	1,50	850 Kg
500	18,19	23,05	1,50	943 Kg

PACKING BAG

Dimensions (mm)	Weight (Kg)
910x480x415	18 Kg
910x480x415	25 Kg
910x480x415	29 Kg
1020x620x635	33 Kg
1020x620x635	37 Kg
1020x620x635	40 Kg
1020x620x635	44 Kg
1020x620x635	46 Kg
1235x820x550	62 Kg
1235x820x550	64 Kg
1235x820x550	73 Kg
1235x820x550	77 Kg
1235x820x750	89 Kg
1235x820x750	103 Kg
1235x820x960	112 Kg
1235x820x960	124 Kg
1235x820x960	132 Kg
1235x820x960	143 Kg
1235x820x960	154 Kg
1235x820x960	165 Kg
1340x940x1080	181 Kg
1340x940x1080	191 Kg
1340x940x1080	198 Kg
1340x940x1080	218 Kg
1340x940x1080	235 Kg
1340x940x1080	252 Kg
1340x940x1080	275 Kg
1340x940x1080	284 Kg
1340x940x1080	292 Kg
1340x940x1080	301 Kg
1340x940x1080	310 Kg
1340x940x1080	319 Kg
1340x940x1080	328 Kg
1340x940x1080	345 Kg
1640x940x1080	369 Kg
1640x940x1080	377 Kg
1640x940x1080	403 Kg
1830x1040x1200	446 Kg
2170x1260x1380	526 Kg
2170x1260x1380	543 Kg
2170x1260x1380	625 Kg
2170x1260x1380	707 Kg
2200x1700x1000	759 Kg
2200x1700x1000	844 Kg
2200x1700x1000	957 Kg
2200x1700x1000	1054 Kg